# 30 INTERNATIONAL





### VisuMotion Software included!

3D Movie Center Library with ActiveX Control A powerful playback Software for various 2D, Stereo and Multi-View 3D formats.

#### DeepOutside3D.Z

Realtime conversion tool for DirectX or OpenGL based games and applications, with a very high performance also on auto-stereoscopic screens!

Software Development Kit (SDK) Create your own 3D programs and make use of our established developer libraries.

## 21.5" Multi-Touch CLD 3D-Display

We are proud to introduce our new glasses-free 21.5" touchscreen display. The screen features the all new CLD 3D optics producing sharp, bright and crisp 3D images. On top of that, it is equipped with infrared based multitouch functionality.

The majority of previous glasses-free 3D screens had a designated viewing distance that is a multiple of human arm's length and hence was not useable for touch screen applications.

With our new 21.5" CLD, we were able to shorten the 3D viewing distance to arm's length while achieving an excellent 3D impression. The apparatus uses 5 new patents/patents pending for the various 3D technology components included.

"The screen can be perfectly used and incorporated into vending machines, kiosks and infotainment systems", said Stephan Otte, Head of Hardware Development in 3D International Europe. "We are very pleased to offer one of the first glasses-free 3D multi-touch display products in the market at an affordable price."

3D International supports all its 3D display products with a full range of useful tools for content creation and playback, real time drivers and other software modules.

### **Technical Details**

Display type: Screen size: Active display area (W/H): Native resolution: Pixel Pitch (RGB-Triplet): Response time: Dimensions (W/H/D): without stand: Number of views: 3D viewing distance:

Connectors:

Power supply: Weight: Multi-Touch CLD 3D-Display 546 mm (21.5") 476,6 x 268,1 mm<sup>2</sup> 1920 x 1080 Pixel (FullHD) 0,248 mm 5 ms 513 x 419 x 263 mm<sup>3</sup> 513 x 332 x 75 mm<sup>3</sup> 5 0,80 m Minimum: Optimum: 1,00 m Maximum: 1,80 m D-Sub (Analog) DVI-D (Digital) 3,5 mm Audio AC 100-240V, 50/60Hz ca. 5,5 kg



 SD International Europe GmbH

 Pruessingstrasse 35

 07745 Jena | Germany

 E-MAIL: info@3di.com.my

 WEB: www.3di.com.my

 PHONE: +49 (0) 3641 69867 0

 FAX: +49 (0) 3641 69867 99



#### 3D International Sdn. Bhd.

No.16 Jalan Industri PBP 9, Taman Industri Pusat Bandar Puchong, 47100 Puchong, Selangor | Malaysia PHONE: +603 8060 0748 FAX: +603 8060 0874